



GENERAL
LIMITED
WARRANTY
Wallscape

GENERAL LIMITED WARRANTY - Wallscape

Details and Definitions for Warranties -----3

General Limited Warranty – Conditions and Owner Obligations ----- 4

General Limited Warranty Details -----5

Wallscape Installation Guide -----8

Wallscape Care and Maintenance Guide -----11

DETAILS AND DEFINITIONS OF WARRANTIES

The warranties outlined below ensure that Welspun's Wallscape wall panels will perform as intended for the duration of the specified warranty period, effective from the product invoice date. This warranty applies when Wallscape panels are installed in accordance with the **Welspun Wallscape Installation Guide**, over approved wall substrates with wall undulation not exceeding **3 mm over a 10-foot length**, using the recommended adhesives, and are properly maintained under normal household use.

Manufacturing Defects Warranty covers manufacturing defects only

- Damage arising from transportation from Welspun to distributor only and should be reported within 7 days of invoice generated by Welspun to the distributor.
- Product construction related issues observed before installation.

Stain Resistant Warranty covers resistance to permanent stain caused by common household products, excluding permanent marker, permanent dyes & finishing stains.

Application areas: Wallscape wall panels are suitable for a variety of residential, commercial, hospitality, and institutional interior walls, including: Living Room, Hotel Rooms, Bedroom, Meeting Room, Reception, Shops, Lobby, Library, Cafeterias.

Design versatility: Straight / Linear Layout – Panels are installed in a straight, aligned pattern to create a clean and seamless wall appearance.

¹ Normal usage refers to common everyday activities in the intended wall application areas, such as residential, hospitality, commercial, and interior walls. It excludes damage caused by intentional misuse, impact, sharp objects, or other abnormal activities.

² For additional use cases, please consult the Welspun customer case for further guidance.



GENERAL LIMITED WARRANTY – CONDITIONS AND OWNER OBLIGATIONS

These warranties only extend to the original end user and are non-transferable. In order to maintain and protect your coverage under the terms of these warranties, it is your obligation to adhere to the following:

1. Keep proof of your purchase in the form of a bill, invoice or bank statement & pre-installation report from your retailer that shows the date of purchase, installation and the price you paid for Wallscape.
2. Welspun warranty applies to first quality products - which are used only for recommended use - for the stated warranty period when installed in accordance with Welspun's Wallscape Installation Guide over approved substrates and wall levelling using the recommended adhesives. The warranty period, when valid, shall begin on the date of product purchase invoice.
3. Inspect wallscape material prior to installation for any imperfections or manufacturing related defects. Welspun's products undergo extensive testing and visual examination in an attempt to assure the shipped wallscape is always first quality. It is the responsibility of the end user to confirm the received material is free of any obvious visible defect that may be detrimental to the appearance and/or performance of the product.
 - Minor color, shade and/or texture variations are normal. They are inspired from nature's existing entropy. Any variances between actual material, product samples and/or brochures should be addressed with your retailer prior to installation. If the retailer determines the condition "unacceptable", Welspun should be informed immediately.
4. When placing furniture or other objects against Wallscape, use smooth, non-staining protective pads or buffers at contact points to prevent scratches, dents, or surface damage. Avoid direct contact with sharp, rough, or metal surfaces. Ensure that any metal fittings or supports in contact with the panel are rust-proof and properly finished.
 - Avoid placing chairs, tables, or other furniture in a manner that may cause repeated impact, rubbing, or abrasion against the Wallscape panels. Use suitable protective buffers where furniture comes into contact with the wall surface.
5. Perform proper cleaning and maintenance regularly and as needed. See Welspun's Wallscape/ Care and Maintenance Guide (page 11) for details.

GENERAL LIMITED WARRANTY DETAILS

What is NOT covered by this Warranty?

1. Product sold by the manufacturer as other than "first quality"
2. Material not installed in accordance with Wallscape Installation Guide (page 8). Improper Installation includes, but is not limited to, issues resulting from the use on undiluted wall level or improper substrate/wall preparation. Installation errors are not manufacturing defects. Welspun does not warrant for installer workmanship.
3. Welspun will not pay for labor costs to repair or replace material with visible defects that were apparent before installation.
4. Improper maintenance, which results in dulling/fading design film.
5. Damage resulting from neglect or misuse of strong detergents, chemicals, corrosives; including but not limited to stains from paints, dyes, mats, fertilizers or other similar materials.
6. Damage caused by moving appliances, heavy furniture, or other objects without adequately protecting the Wallscape panels. When moving or installing heavy objects near Wallscape, take appropriate precautions to prevent impact, scratching, abrasion, or other damage to the panels. Use suitable protective boards, padding, or barriers where necessary.
7. Damage resulting from accidents, casualty events, abuse, or improper use, including pet-related damage such as chewing, scratching, or clawing. Accidents, abuse, and improper use include, but are not limited to, damage caused by impact from heavy or sharp objects, cuts, scratches, dents, burns, excessive heat, drilling or hammering, improper cleaning, unprotected furniture or fixtures, and other mechanical or physical damage to the Wallscape.
8. Damage caused by impact or mechanical loads, including impact from moving furniture, appliances, equipment, carts, or other heavy objects against the Wallscape
9. Damage caused by water leakage, plumbing leaks, excessive moisture, or water penetration behind or onto the Wallscape.
10. Damage or neglect during transportation.
11. Damage arising because the Wallscape is installed in an outdoor area, a solarium, a porch, a garage or areas similar to all of these.
12. Damage caused by an act of God (for example a natural disaster).
13. Fading, discoloration, or other damage due to excessive temperatures, burning flame or sunlight. Room Temperature must not exceed 113 ° F (45°C).
14. Problems or damage due to excessive moisture or hydrostatic pressure from the sub-wall including pH levels outside the limits set out in Welspun's Wallscape/ Installation Guide.
15. Discoloration caused by contact with rubber, latex, or other staining materials. Some rubber- or latex-containing products may cause discoloration or staining of the Wallscape surface. Always use non-staining, Wallscape-compatible protective pads or materials where contact with the panel may occur.
16. Discoloration caused by direct contact with rubber, latex, or other staining materials, including rubber pads, wheels, rollers, or similar components. Use suitable non-staining protective materials wherever contact with the Wallscape surface may occur.
17. Re-installation of an already installed product, is not covered by warranty terms.
18. Accessories and other fitments of a brand different than Welspun, which is installed by the customer is not covered.

³ The installation manual is reviewed on a regular basis, and wallscape must be installed according to the recommendations that are current and available at the time of installation

⁴ Welspun does not recommend direct contact of furniture or other movable objects with Wallscape panels. Use suitable protective buffers or pads wherever contact may occur to prevent scratching, rubbing, or impact damage.

GENERAL LIMITED WARRANTY DETAILS

Warranty Remedy

If your Welspun Wallscape fails to perform as stated in the applicable Welspun Wallscape General Limited Warranty, Welspun will determine whether it will assist in the repair of the defective area or supply new Welspun Wallscape or any part thereof of the same color, design or grade if available. If unavailable or discontinued, Welspun reserves the right to select and supply similar Welspun Wallscape material. At times, it may be necessary to contract a Certified Inspector to determine unknown causes; Welspun reserves the right to determine if this action is necessary or not.

1. If Welspun authorizes repairs or replacement of a section as a result of a warranty claim, you will be required to clear any items placed over the affected area subsequent to the original installation. Welspun will not credit or reimburse cost associated with the removal of these items.
2. Labor reimbursement and product reimbursement will not be considered for installation not adhering to the Welspun's Wallscape Installation Guide.
3. Warranty coverage for a replacement of wallscape will be limited to the remaining portion of the original warranty.

Consequential or Incidental Damages

Welspun excludes and will not pay consequential or incidental damages under these warranties.

Welspun will not credit or pay for any loss, expense, or damage, beyond the wallscape itself, that may result from a manufacturing related defect in the examples of consequential or incidental expenses or damages are replacement of wall substrate or underlayment, accessories, disconnecting/reconnecting appliances or fixtures as well as moving of furniture.

Welspun does not allow or authorize any other person or entity to alter the obligations and limitations in this warranty. This warranty is the complete and exclusive expression of our warranty and is in lieu of all other express and /or statutory warranties.

Welspun reserve the right to inspect the wallscape and to remove samples for additional evaluation, if we consider this necessary. Welspun shall have the sole right to determine or decide the validity of any warranty claim in accordance with terms contained herein. Any attempt to repair or replace the wallscape without our consent will void this warranty.

NOTE: *If your wall is replaced because of discoloration due to "bottom up staining" or mould or mildew growth, this is considered a site-related condition and the replacement wall will not be warranted against future discoloration or staining.*

There are no warranties beyond this expressed warranty. All other warranties including implied warranties, warranties of merchantability or fitness for a particular use, are excluded.

For details on how to file a claim, please refer to our "How to File a Claim" Section (page 6)

⁵ *The installation manual is reviewed on a regular basis, and wallscape must be installed according to the recommendations that are current and available at the time of installation.*

GENERAL LIMITED WARRANTY DETAILS

The following prorated schedule applies to labor costs and material value for Welspun Wallscape, to be borne by Welspun:

LABOUR REIMBURSEMENT PRORATION (Reasonable Labor Costs – based on Prevalent Market Rate)		
	<u>Wallscape</u>	
	Residential	Commercial
1 st Year	100%	100%
2 nd Year	50%	50%
3 rd Year	0%	0%
4 th year – 5 th year	0%	0%

MATERIAL PRORATION		
	<u>Wallscape</u>	
	Residential	Commercial
1 st Year	100%	100%
2 nd Year	50%	50%
3 rd Year	20%	0%
4 th year – 5 th year	10%	0%

How to file a Claim

If you find a defect or other matter covered by any of the limited warranties described previously, notify the retailer who sold you the wallscape covering material within 7 days of discovery of such defect. This Warranty is limited to the designs, colors, structures and styles available at the time of repair or replacement. If the original is no longer available, Welspun has the right to substitute another design, color, structure and style that is similar to the original and that has a similar purchase value. The purchase value is defined as the MRP of the product, or the discounted rate provided to the customer, whichever is lower.

The retailer will review and if necessary, file a claim with Welspun and help you answer any questions you may have. After a warranty claim is properly registered, Welspun's service coordinator will designate a representative to evaluate the warranty claim. This warranty is conditioned upon your reasonable cooperation with Welspun and its service coordinator and representative in the evaluation of your warranty claim and the implementation of any remedy.

Upon approval of warranty claim, 7 days tenure will be provided by Welspun to you to accept the claim, failing which limited warranty will be deemed waived.

What will you need to provide?

- Proof of your purchase in the form of a bill, invoice or bank statement & pre-installation report from your Welspun retailer & Installation Team that shows the date of purchase and price you paid for the Wallscape.
- A detailed description of the defect and/or a photograph or sample of the Wallscape that clearly shows the defect.
- Additional information requested by Welspun to understand the root cause of the issue.

Disclaimer:

Samples, description, and other information concerning the product contained in our catalogues, advertisement, or other promotional material or statements made by sales representatives or distributors are for general informational purposes only and are not binding upon us. No sales representatives or distributors shall have any authority whatsoever to establish, expand or otherwise modify these warranties.

WALLSCAPE/ INSTALLATION GUIDE

Materials Required for Installation: Tape Measure, Square Ruler, Utility Knife, and Chalk Line Etc. (Refer Installation Manual Document)

Acceptable wall substrate

Wallscape products can be installed directly over most existing smooth, sound, clean, and dry wall surfaces, provided the substrate is properly prepared. The acceptable wall substrates include:

- Cement plastered walls
- Gypsum/plasterboard walls
- Flat Concrete levelled walls
- Ceramic or vitrified tiled walls
- Existing painted walls with sound, well-adhered paint
- Other smooth, rigid, and structurally sound wall surfaces

The humidity needs to be checked at five random spots in an area of 100 square ft., and the average value should be less than 2.5% CCM (and less than 75% RH).

Wall Substrate and Wall/Door Preparation

- **Cut the Panel:** Score the Wallscape panel along the required cutting line using a sharp utility knife. Make multiple passes as necessary, then carefully snap the panel along the scored line.
- **Install the Adjoining Panels:** Install the adjoining Wallscape panel's one panel at a time. Carefully position each panel, aligning it with the previously installed panel and maintaining the required joint. Repeat the process until the wall area is completely covered.

Wallscape Panel Replacement – Should one of your Wallscape panels become damaged and require replacement, follow the instructions below

1. **Score the Damaged Panel:** Using a sharp utility knife, carefully score the surface of the damaged Wallscape panel along its length. Make multiple passes as necessary to cut through the surface layer and into the panel core.
2. **Prepare the Wall Substrate:** Carefully remove the damaged panel and any remaining adhesive from the wall substrate using a suitable scraper and adhesive remover. Ensure the wall substrate is clean, dry, smooth, levelled, and free from dust or loose material before proceeding.
3. **Dry Fit the New Panel:** Before applying adhesive, dry-fit the replacement Wallscape panel to ensure a proper fit and alignment with the adjacent panels. Trim the panel edges if required using a suitable cutting tool.
4. **Apply Adhesive:** Use the manufacturer-recommended synthetic rubber-based adhesive. Follow the adhesive manufacturer's instructions regarding open time and installation requirements. Apply the adhesive evenly to the prepared wall surface within the repair area.
5. **Install the New Panel:** Carefully position the replacement Wallscape panel on the prepared wall surface, aligning it with the adjacent panels. Press it firmly into place to ensure full and uniform contact with the adhesive.
6. **Secure the Panel:** Apply even pressure over the panel surface using a suitable hand roller or recommended installation tool to remove air pockets and ensure proper bonding.
7. **Clean Up:** Immediately remove any adhesive residue from the Wallscape panel surface using a clean, damp cloth before it dries. Do not disturb the repaired panel until the adhesive has cured in accordance with the adhesive manufacturer's recommended curing time.

PLEASE NOTE: Warranty exclusions apply to damage caused by impact, mechanical force, or contact with furniture, fixtures, equipment, or other objects. In areas where Wallscape panels may be exposed to frequent impact or contact, appropriate protective measures should be taken to reduce the risk of panel damage or joint separation. However, the warranty does not cover problems resulting from improper use, impact, or mechanical damage.

⁶ Existing painted or coated wall surfaces should be free from plasticizer-containing materials and other substances that may adversely affect the adhesion of Wallscape panels.

WALLSCAPE/ INSTALLATION GUIDE

Introduction

Wall coverings designed and produced by Welspun Flooring, such as Wallscape, are interior wall panel products designed for adhesive installation on suitable wall substrates, in compliance with applicable regional standards and regulations.

Prior to Installation

- Wallscape must be stored vertically on a flat surface in a dry and ventilated area. Do not store it in very cold (less than 0°C) or very warm (more than 40°C) or humid areas.
- Despite the care and rigor during production, a visual inspection of the materials before installation is recommended, such as color, design, and for differences or defects, to prevent installation of false materials.
- In case any visual faults are detected on materials, do not install the faulty products and contact your local dealer, to obtain information about the way forward.
- Welspun recommends installation of products within the same batch/lot number in the same area.
- In any case, store the boxes standing up and do not store laying down flat or leaning the boxes on the wall.
- Wallscape needs to follow proper acclimation process. Welspun recommends to leave the materials at the installation site at least for one day at room temperature (18°C~40°C) to obtain perfection in installation. Similar temperature and time are required for adhesives as well.

Suitable wall substrate

- Wallscape installation requirements must comply with applicable regional standards, regulations, and norms.
- Wall substrate analysis and preparation are the responsibility of the installer.
- Welspun shall not be held responsible for damage to Wallscape panels resulting from an unsuitable, improperly prepared, or defective wall substrate.
- Any previously installed wall coverings, loose finishes, wallpaper, or other materials that may affect adhesion must be completely removed before installation.
- The wall surface must be thoroughly cleaned to remove dust, dirt, grease, contamination, loose particles, and other foreign substances that may interfere with proper installation.
- The installation area must be sufficiently cured and free from excessive moisture before installation.
- The wall substrate must be smooth, flat, dry, clean, sound, and structurally stable. Any significant surface irregularities, cracks, holes, or undulations must be properly repaired before installation.
- Wall moisture/humidity must be checked at appropriate locations before installation. The substrate must meet the moisture and humidity requirements specified by the adhesive manufacturer and applicable installation guidelines.

Start of Installation

It is your responsibility to inspect the wall prior to installation to ensure that there are no visual defects. Do not install with visible defects and undulation more than a limit suggested above. If visible defects are present, contact your retailer immediately.

- Wall must be clean, smooth, flat and dry before installation.

The advantage of Welspun's Wallscape product is its installation flexibility, allowing the installer to select the starting position and installation direction according to the wall layout. The panels can be installed one panel at a time, providing greater flexibility during installation.

Installation:

➤ Wallscape installation must follow the regional requirements.

- i. Most common installation methods based on the dimension of the products are as follows: 1/3 or 1/2 step installation.
- ii. Most common installation method for SPC wall panels is straight installation, with the panels aligned vertically or horizontally according to the product dimensions and design requirements.
- iii. The amount of applied adhesive may vary depending on the wall condition. Spread the right amount of adhesive evenly over the wall substrate and backside of the product, let it tack -off (open time) until it reaches its initial bonding strength. Always read the adhesive manufacturer's instructions.
- iv. Lay the Wallscape product, into the tacked - off adhesive, in order to transfer the adhesive fully onto the backing.
- v. Cut the Wallscape product, free of tension, against the wall.
- vi. Do installation in a manner that water or moisture cannot penetrate below the product back.
- vii. To ensure full contact with adhesive, immediately press every panel with a rubbing block or hand roller.
- viii. Clean adhesives stains with a damp cloth. Wipe any excess sealer that comes to the surface of the wallscape with a damp cloth and follow with a dry cloth to assure all sealer is removed from wallscape surface.

WALLSCAPE/ INSTALLATION GUIDE

➤ Protection and open to traffic

The Wallscape product must be protected from impact, vibration, moisture, and other disturbances for 72 hours after installation to allow the adhesive sufficient time to stabilize and achieve proper bonding.

All activities that may disturb the installed panels, including furniture installation, drilling, fixing, movement of heavy objects, or other work in close proximity to the wall, should be postponed for at least 72 hours after installation.

➤ First Cleaning after installation

- i. Prior to opening the area for normal use, Welspun recommends cleaning the Wallscape panels using a soft, dry or slightly damp, lint-free cloth to remove any dust or installation residue.
- ii. To keep the Wallscape product in perfect condition, Welspun recommends frequent cleaning and maintenance with the right cleaning process.
- iii. During furniture installation or movement, Welspun recommends taking appropriate precautions to protect the Wallscape panels from accidental impact, scratching, or other surface damage. Furniture and other objects should be handled carefully and kept from coming into direct contact with the installed panels.
- iv. The product should be protected from prolonged exposure to direct sunlight. Windows and glass doors should be adequately covered or protected to minimize prolonged direct sunlight exposure to nearby Wallscape panels and help prevent discoloration or fading.).
- v. If the Wallscape panels are installed near exterior access doors or windows, appropriate measures should be taken to minimize the transfer of dust, dirt, and moisture into the area and prevent these contaminants from coming into contact with the panels.
- vi. For additional information or advices about cleaning and protection, please refer to Welspun's cleaning guidelines.

⁷ Welspun will not be held responsible for problems that may arise for approved secondary alternative seam sealers. Please contact the approved secondary alternative seam sealer's manufacturer with issues

WALLSCAPE/ CARE AND MAINTENANCE GUIDE

Your Welspun Wallscape is not only beautiful, but durable. It is also much easier to maintain than most other Wall panel products, thanks to its tough protective finish and moisture resistance. Only takes a few simple care and maintenance steps to keep your Wallscape looking beautiful for years to come.

Preventative Maintenance Guidelines:

- Prevent scratches and dents: Use suitable non-staining protective pads or buffers at points where furniture, fixtures, or other objects may come into contact with Wallscape panels.
- Protect from excessive moisture: Do not expose Wallscape panels to excessive water, prolonged moisture, or standing water.
- Protect from dirt and contaminants: Keep Wallscape panels protected from dirt, grease, mud, and other contaminants, particularly in areas near entrances or high-traffic zones. Clean the panels regularly using recommended cleaning methods.
- Avoid contact with tar or asphalt: Prevent tar, asphalt, or other staining substances from coming into contact with the Wallscape surface.
- Protect against heat and burns: Keep cigarettes, matches, flames, hot objects, and other sources of excessive heat away from Wallscape panels, as they may cause permanent discoloration or surface damage.
- Avoid prolonged direct sunlight: Prolonged exposure to direct sunlight may cause gradual discoloration or fading of the Wallscape surface. Where appropriate, use curtains, blinds, or other suitable measures to minimize prolonged direct exposure.

Cleaning & Maintenance Guidelines:

- **Regular Cleaning:**
Use a soft-bristle broom, a dry microfiber mop, or a vacuum cleaner with a soft brush attachment to remove loose dirt, dust, and debris. Regular cleaning prevents abrasive particles from scratching the surface of the Wallscape product.
- **Damp Cleaning:**
When cleaning Wallscape panels, use a soft, well-wrung damp cloth or microfiber cloth with a mild, pH-neutral cleaner suitable for the panel surface. Avoid ammonia-based, abrasive, solvent-based, or harsh chemical cleaners, as they may dull, stain, or damage the surface finish. Do not soak the panels or apply excessive water. Wipe away any excess moisture immediately, particularly around panel joints and edges.
- **Spill Clean-up:**
Promptly clean up spills using a soft cloth or sponge. Avoid using harsh chemicals or abrasive scrubbers, as they can damage the wall's surface and it is important to be cleaned up immediately.
- **Avoid Standing Water:**
While wallscape is water-resistant, exposure to standing water can damage the wall. Immediately wipe up any spills or standing water using a dry cloth or mop. Do not allow water to seep into the seams or edges of the panel.
- **Furniture Protection:**
Use suitable non-staining felt pads, protective buffers, or furniture glides at contact points between furniture and Wallscape panels to prevent scratching, scuffing, or indentation marks. When installing or moving furniture near Wallscape panels, handle it carefully and avoid impact or direct contact with the panel surface.
- **Avoid Sharp Objects:**
Avoid dropping, striking, or placing sharp or heavy objects against Wallscape panels, as they may cause scratches, dents, gouges, or surface damage. Use caution when handling or moving items near the panels to prevent damage.
- **Routine Maintenance:**
Regularly inspect the Wallscape panels for signs of wear, surface damage, scratches, stains, discoloration, or loose panels. Any damaged, defective, or loose panels should be repaired or replaced promptly to maintain the appearance and integrity of the wall installation. Follow the manufacturer's recommended guidelines for cleaning, repair, and panel replacement.
- **Protect from Sunlight:**
Direct sunlight can cause fading or discoloration of wallscape over time. Use window coverings such as blinds or curtains to minimize exposure to sunlight, especially in areas with large windows or glass doors.

WALLSCAPE/ CARE AND MAINTENANCE GUIDE

DO NOT use the following on your Welspun Wallscape:

- Soap-based detergents or harsh cleaning agents
- Abrasive cleaners, scouring powders, or rough cleaning pads
- Wax, polish, or shine-enhancing products
- Mineral oils, solvents, or petroleum-based products
- Ammonia, bleach, or other strong chemical cleaners
- Sharp tools, abrasive materials, or hard-bristled brushes that may scratch the panel surface
- Excessive water or steam cleaning

Always read the cautionary information on all cleaners prior to use.

IMPORTANT: Avoid impact from sharp, heavy, or hard objects on Wallscape panels, as this may cause scratches, dents, or surface damage.

How to Treat Stains, Spills & Scuffs?

Follow the remedies in order. Unless instructed otherwise, use a clean, white cloth or towel. Always rinse the affected area with clean water after treatment.

Stain or Spills caused by acids, alkalis, blood, food dressings, mustard, food, fruit, fruit juices, candy, cleaners, strong soaps, dye, dye markings, urine and faeces, grass, iodine, mercurochrome and rust.

The Remedy

- First, remove as much solid material as possible.
- Scrub area with cleaner full strength.
- Rub the area with a 10/1 dilution of water/liquid bleach.
- Rub the area with isopropyl alcohol.
- If rust stain does not respond, use lemon juice or a cream of tartar solution.

Paint & Solvent Spills caused by dry cleaning fluids, lacquer and latex paint, nail polish, solvents, oil-based paints, wood stains and varnish.

The Remedy

- If substance is dry, gently peel it from the wall. Avoid sharp instruments that can scratch wallscape.
- Scrub area with non- abrasive cleaner.
- Rub lightly with odorless mineral spirits or paint thinner.

NOTE: Do not use acetone or nail polish remover!

Substances that won't wipe up such as adhesives, chewing gum oil, grease, candle wax and tar.

The Remedy

- First, remove as much solid material as possible.
- Carefully remove excess with a spoon or fingernail.
- Scrub area with non-abrasive cleaner.
- Rub lightly with odorless mineral spirits, isopropyl alcohol or lighter fluids.

Damage or surface marks caused by scuffing, rubbing, abrasion, or smudging from contact with furniture, equipment, tools, or other objects.

The Remedy

- Rub the scuff with fingertip, rubber will come right off. The friction from the rubbing will remove rubber.
- Scrub area with non-abrasive cleaner.
- Rub lightly with isopropyl alcohol or lighter fluid.

CAUTION!

Isopropyl alcohol, lighter fluid, odorless mineral spirits and paint thinner are flammable solvents. Carefully read and follow cautionary information on their respective labels. Keep traffic off treated area for 30 minutes.

⁸ For spot treatment, a diluted 10/1 solution of water/liquid bleach is tolerable for stain removal